

**High-quality and cost-effective. Essential functions.
Complies with IEC standards.**

Sound Level Meter NL-28

Industrial safety and health



General noise measurement



Useful for:

Occupational safety and health, construction, traffic, karaoke/bars, factories, schools, hospitals, car inspections, HVAC, etc.

Easy-to-read OLED display



〈Actual size〉

Easy to use with one hand. The non-slip design makes it easy to grip. Button layout provides intuitive operability.



NEW

Equipped with USB Type-C connector



By connecting the USB Type-C connector and PC with a cable, data measured with the NL-28 can be acquired as a CSV file.

NEW

Automatic calibration function

- Convenient for sound calibration before and after measurement. Insert the microphone into the acoustic calibrator and calibration is performed automatically.
- Calibration history data can be stored.



■ **Conforms to IEC 61672-1:2013 class 2, JIS C 1509-1:2017 class 2, JIS C 1516:2020 class 2**

■ **Pause measurement function to remove unwanted noises for measurement evaluation.**

■ **Continuous operation time is over 9 hours with two AA batteries (Compatible with alkaline batteries, NI-MH rechargeable batteries)**

■ **At the selected time weighting, the following calculation values can be measured simultaneously.**

Measurement function	A-weighting	C-weighting
Time-weighted sound level L_p	●	●
Equivalent continuous sound level L_{eq}	●	●
Maximum time-weighted sound level L_{max}	●	●
Sound exposure level L_E	●	●
Peak sound level L_{peak}	—	●

Specifications

Applicable standards	IEC 61672-1:2013 class 2 JIS C 1509-1:2017 class 2 JIS C 1516:2020 class 2 CE Marking • EMC Directive Directive 2014/30/EU EN 61326-1:2013 • RoHS Directive Directive 2011/65/EU EN IEC 63000:2018 UKCA Marking, China RoHS, KC Mark
Measurement function	At the selected time weighting, the following calculation values can all be measured simultaneously at the frequency weighting A and C. (For L_{peak} , only the C-weighting can be measured.)
Instantaneous value	Time-weighted sound level L_p
Calculated values	Equivalent continuous sound level L_{eq} Sound exposure level L_E Maximum time-weighted sound level L_{max} Peak sound level L_{peak}
Microphone	Model: UC-52 Sensitivity level (representative value): -33 dB (re. 1 V/Pa at 1 kHz)
Measurement level range	A-weighting: 30 dB to 137 dB, C-weighting: 36 dB to 137 dB, C-weighted peak sound level: 65 dB to 140 dB
Self-generated noise	A-weighting: Max. 24 dB (Typical 22 dB), C-weighting: Max. 30 dB (Typical 28 dB)
Measurement frequency range	20 Hz to 8 kHz
Frequency weighting	A-weighting, C-weighting
Time weighting	F (Fast), S (Slow)
Calculation interval	L_p, L_{max}, L_{peak} : 20.8 μ s (sampling frequency 48 kHz) L_{eq}, L_E : 1 s

Calibration	A reference signal is input using sound calibrator NC-75/NC-74 or pistonphone NC-72B/NC-72A, and the signal input sensitivity is adjusted automatically or manually. Up to 999 calibrations can be managed in the calibration history and saved. * With auto-calibration, only the sound calibrator NC-75/74 can be used.
Windscreen	Conforms to IEC 61672-1 class 2, JIS C 1509-1 class 2, and JIS C 1516 class 2, even when a windscreen is attached.
Display	1.5-inch monochrome organic EL display Resolution: 128x128 Numeric value update cycle: 1 s, Bar graph update cycle: 100 ms
Store	Manually starts or stops measuring and simultaneously calculates L_{eq}, L_E, L_{max} and L_{peak} before recording the results in a file. Store data can be confirmed on the recall screen.
Data storage capacity	Internal memory: Can store up to 200 data sets
Measurement time	1 min, 5 min, 10 min, 1 h
USB	Internal memory can be recognized by the computer as a removable disk for data transfer.
Power supply	AA battery x2 Operating time (23 °C, measurement status) Alkaline battery: Approx. 9 hours, Ni-MH rechargeable battery: Approx. 9 hours * The operating time with batteries will vary depending on the battery manufacturer and type (model), the usage environment of NL-28, and the measurement conditions.
Operating temperature and humidity range	Temperature: -10 °C to 50 °C Humidity: 10 % to 90 % RH (no condensation)
Dimensions, weight	Approx. 200 mm (H) x 50 mm (W) x 34 mm (D) Approx. 160 g (including batteries)
Accessories	Windscreen WS-14 x1, Windscreen fall prevention rubber x1, Hand strap x1, USB port cover x1, Size AA alkaline batteries x2
Optional accessories	Sound calibrator NC-75, Pistonphone NC-72B, Tripod for sound level meter ST-80



JCSS
JCSS 0197

RION CO., LTD. is recognized by the JCSS which uses ISO/IEC 17025 as an accreditation standard and bases its accreditation scheme on ISO/IEC 17011. JCSS is operated by the accreditation body (IAJapan) which is a signatory to the Asia Pacific Accreditation Cooperation (APAC) as well as the International Laboratory Accreditation Cooperation (ILAC). The Quality Assurance Section of RION CO., LTD. is an international MRA compliant JCSS operator with the accreditation number JCSS 0197.

* Windows is a trademark of Microsoft Corporation. * Specifications subject to change without notice.

Distributed by:

VibrAkustik ApS
www.vibrakustik.dk
info@vibrakustik.dk
+45 60631210

RION CO., LTD.
https://rion-sv.com/

3-20-41, Higashimotomachi, Kokubunji, Tokyo 185-8533, Japan
Tel: +81-42-359-7888 Fax: +81-42-359-7442