[♦]VIQUA IHS22-E4

Ultraviolet Water Systems from VIQUA

The **PROFESSIONAL family** of compact UV water systems with integrated pre-filtration provide a **reliable** and **economical** way to treat drinking water in virtually any residential application. VIQUA's products have been designed and tested to ensure quality drinking water is at everyone's finger tips.

To address recent concerns around lead contamination of drinking water, our classic IHS systems now feature lead reduction capability, offering a more complete water treatment system for your home.

Regardless of your need, there is a VIQUA system to suit your requirements. The VIQUA IHS22-E4 offers a maximum flow rate of 22 GPM (5 m³/hr), which is ideal for many small businesses and public facilities.



Features of VIQUA UV water systems

- The special lamp plug ensures that no one can power the UV lamp if it's not in the UV chamber.
- Specially designed and tested lamps provide consistent and reliable ultraviolet output over the entire life of the lamp (9000 hours) to ensure continuous purification, and offer superior performance in a wide range of water conditions.
- System comes supplied with sediment filter to remove particles commonly found in water and carbon block filter to remove lead and reduce odours, colour. Reduces the need for expensive pre-treatment systems.
- The system comes equipped with high flow filters allowing the water pressure to remain consistent.
- Bracket is made of heavy gauge steel that is powder coated for both durability and aesthetics.
- **NEW** LCD controller features a large backlit display for easy reading, simultaneously displaying lamp life remaining, support contact information, and lamp replacement reminder that indicates when the lamp needs to be replaced, ensuring continued water safety. The intuitive, user friendly menu is dealer programmable and allows the user to quickly find the replacement parts needed for the system by using the replacement parts menu, dealer contact information, as well as on board quick-reference instructions for system troubleshooting.

Specifications





MODEL	IHS22-E4; IHS22-E4/2; IHS22-E4/2A; IHS22-E4/2B
FLOW RATES (@ 95% UVT)	
US Public Health (16 mJ/cm²)	-
VIQUA Standard (30 mJ/cm²)	22 GPM (83 lpm) (5.0 m³/hr)
NSF/EPA (40 mJ/cm²)	16 GPM (60 lpm) (3.6 m³/hr)
DIMENSIONS	
Overall	25" x 12" x 36.5" (63.5 cm x 30.5 cm x 92.9 cm)
Controller	8.5" x 6" x 3" (22 cm x 15 cm x 7.6 cm)
Inlet/Outlet Port Size	1" FNPT/MNPT
Shipping Weight	38 lbs (17.3 kg)
ELECTRICAL	
Voltage	100-240V / 50/60 Hz
Power Consumption	83 W
Maximum Operating Pressure	100 psi (6.89 bar)
Influent Water Temperature	2-40°C (36-104°F)
FEATURES	
Visual "Power On"	YES
Chamber Material	304 SS
Visual Lamp Life Remaining	YES
Audible Lamp Failure	YES
Audible Lamp Replacement Reminder	YES
High-Flow Sediment Filter	20"
High-Performance Carbon Filter	20"
Solenoid Valve	Optional (650717-002)

Replacement Parts

602806 - UV lamp for IHS22-E4 **602733** – quartz sleeve IHS22-E4 **650733R-001** – controller for IHS22-E4 CMB-520-HF - dirt/rust cartridge for IHS22-E4 C2-02PB – taste/odour/lead cartridge for IHS22-E4

Water Quality Parameters

Hardness Iron **Tannins** < 7 grains (120 mg/L) < 0.3 mg/L< 0.1 mg/L









