

DANOfile

DEMOUNTABLE HYGIENE CEILING

- ✓ Clean-room and ISO certified hygiene ceiling
- ✓ Ergonomic installation
- ✓ Certified fire resistance up to 30 minutes
- ✓ Sustainable

FEATURES



- T-grid ceiling
- Hygiene ceiling
- Laminated surface
- Anit-static
- Washable surface

SUSTAINABLE PRODUCT:

- Made of gypsum
- Safe material
- 100% recyclable
- Improved indoor climate



PRODUCT SPECIFICS

| | | |
|---|---|---|
| EDGE DESIGN & TILE THICKNESS |  6.5mm S15/24 6.5mm lay-in tile in exposed grid |  9.5mm S15/24 9.5mm lay-in tile in exposed grid |
| TILE WEIGHT, kg/m² | 6.90 | 7.90 |
| SIZES, mm | 600 x 600 600 x 1200 | |
| SURFACE TREATMENT | Front: Foil-covered with pre-impregnated, non-toxic white paper RAL 9016 (NCS S0300-N, gloss 10) Back: PE foil | |
| SYSTEM COMPONENTS | 1) Gypsum ceiling tile, 2) T15/38 or T24/38 main runner, 3) Cross tees, 4) Hangers | |
| CERTIFICATES | 1) Environmental product declaration, 2) FDES – life cycle analysis, 3) Danish Indoor Climate Labelling | |

PRODUCT PERFORMANCE

FIRE RATING

- B-s1, d0
 - 30 minute fire resistance (6.5mm thickness)
 According to BS476:Part 23:1987, Clause 5, on a Suspended Assembly Protecting Loadbearing 'I' Section Steel Beams

HYGIENE

Classified as ISO 5 - Tested for airborne particles in accordance with ISO 14644-1
 Can stand rigorous cleaning with concentrated disinfectants and detergents with a very high pH (up to pH 13.0) and a very low pH (down to pH 2.5).

LIGHT REFLECTION

86.3%

AIR QUALITY

Indoor value: 10 days
 Particle emission: LOW

AMBIENT CONDITIONS

Can withstand:
 - constant RH 70% and 25°C
 - periodic RH 90% and 30°C
 - ambient temperatures of up to 50°C.

LOAD-BEARING CAPACITY

9.5 mm tile: Supports direct built-in fixtures up to 3 kg/m².
 6.5 mm tile: Reinforcement panel required for built-in fixtures.

ROBUSTNESS

Glass fibre reinforced gypsum. High pressure resistance. Highly stable ceiling ensured by tile density.