

A 1 temperature cabinet adjustable from 6°C to 18° to mature your wines in the best possible conditions.



Code: MA1TMV3

Internal layout: SHELVES

Storage shelf: AXUHT Weight: 1,8 kg

Dimensions (WxDxH): 535 x 525 x 28 mm

Type of structure: slats **Number of bottles**: up to 77

Material: Solid Beechwood coated with an ecological water varnish.



« Storage»
77 Bottles

Sliding shelf: ACUPHT

Weight: 4 kg

Dimensions (WxDxH): 533x529x27 mm

Type of structure: table

Number of bottles: up to 12

Material: Steel and PS shock



« Sliding»
12 Bottles

| Pack Type (sliding + storage shelves) | Pack Sliding | Storage Capacity |
|---------------------------------------|--------------|------------------|
| 166 | 141 | 168 |
| 2 storage 2 sliding | 10 sliding | 3 storage |

* Maximum capacity

** Empty wine cabinet

*** Traditional Bordeaux bottles

**** With the rear stop, without the handle

Range: PRESTIGE

Model : Manoir Glass door

Function: Ageing

Capacity*: 168 Bottles***

Combine technology/ performances and protection of the environment.

A constant temperature thanks to a double hot-cold regulation.

New glass door with double panel reinforced with Argon gas for a better insulation and to filter up to 97% of U.V. rays. It will also lower the condensation risks.

Suitable hygrometry thanks to a warmer and wetter air supply.

Air circulation ensured by the principle of thermodynamic pump.

No vibration thanks to the slow-cycles compressor fixed on silent blocs.

Storage or sliding shelves.

TECHNICAL BENEFITS

GENERAL FEATURES

| Gross weight, packaged(Kg) Net weight (Kg)** Dimensions in packaging H x W x D (mm) Dimensions H x W x D(mm) | 87 77 1564x733x768 1479x680x720**** |
|--|--|
| Energy efficiency rating Acoustic emissions (dB(A)) Acoustic emissions class Consumption per 24h (KWh) Annual energy consumption Aec (kWh/year) Ambient temperature operating limit (°C) Useful volume (L) | G 37 C 0,42 154 0-30 360 |

- ✓ Electronic regulation. (1T = 6-18°C).
- \checkmark Internal temperature display on the digital screen.
- √ Low energy consumption (59mm PU foam).
- \checkmark Visual alarms: Temperature sensor defect, Temperature level (when too high or too low), Hygrometry (when too low, for 1 temp. only).
- \checkmark Lighting system: 3 options: Permanent lighting, Lighting when door opening, No lighting.
- ✓ Double Hot/ Cold circuit > Automatic « Winter function ».
- $\checkmark\,$ Hygrometry ensured by the principle of thermodynamic pump.
- ✓ Anti-UV protection (for glass door only).
- √ 2 adjustable feet (front).
- ✓ Lock system.
- √ Storage grid in the lower part.
- \checkmark Black and Silver stainless steel handle. Removable.
- ✓ Reversible door (glass door only).
- ✓ Inner material: Stucco Aluminum.
- ✓ Compressor R600a Gas.
- ✓ Colors : Black or Tobacco.

