

TECHNICAL DATASHEET – 60 m³ Mud tank

Serial Number: CTDMS P 1/8



Pump motor power ea.:	75-88kW, 400/440, 50/60 Hz
Transfer pump capacity:	1450 RPM / 3m ³ – 1750rpm / 3,9m ³ per. min
Agitator mix capacity:	18m ³ pr. min
Inlet / outlet connection:	4'' WECO FM fig 206 / 4'' WECO FM fig 206
Design pressure:	Atmospheric storage vessel
Holding capacity:	1 x 20m ³ & 1 x 40m ³
Lifting certification:	DNV 2.7-3
Dimension (L x W x H):	9,39 x 4,05 x 5 meter
Weight:	27 500 kgs
Area classification:	Zone 1
Build standards:	NORSOK Z-015, S-002, Machine Directive, ATEX and CE. II 2G IIA T4.

The tank has two compartments to allow for two different mud weights to be stored. The tank is continuously agitated to maintain adequate mixing and prevent settling of weight agents.

TECHNICAL DATASHEET – 60 m³ Mud tank

Serial Number: CTDMSPP 1/9



Pump motor power ea.:	75-88kW, 400/440, 50/60 Hz
Transfer pump capacity:	1450 RPM / 3m ³ – 1750rpm / 3,9m ³ per. min
Agitator mix capacity:	18m ³ pr. min
Inlet / outlet connection:	4" WECO FM fig 206 / 4" WECO FM fig 206
Design pressure:	Atmospheric storage vessel
Holding capacity:	1 x 20m ³ & 1 x 40m ³
Lifting certification:	DNV 2.7-3
Dimension (L x W x H):	9,39 x 4,05 x 5 meter
Weight:	27 500 kgs
Area classification:	Zone 1
Build standards:	NORSOK Z-015, S-002, Machine Directive, ATEX and CE. II 2G IIA T4.

The tank has two compartments to allow for two different mud weights to be stored. The tank is continuously agitated to maintain adequate mixing and prevent settling of weight agents.